



OCULAR

Ocular LTE Universal Type 2 socket



Model: OC20-BA-7.2KW
OC20-BA-22KW

Ocular LTE Tethered 6 Meter Type2 cable



Model: OC20-BC-7.2KW
OC20-BC-22KW




LCD



LED Flash



Button
Switch



PC-ABS
Material

This is a simple wallbox that comes in 2 variants: Universal and Tethered, referring to the way the EV is connected. It comes with a colourful LCD display that allows users to clearly see the current charging status including charging time, voltage, current internal temperature etc.

Non-hardware faults that occur during charging will be automatically fixed. Faults that require manual repair will be displayed on the LCD screen. The housing is sturdy and has an IP66 rating.

It can be easily installed on the wall. If the customer prefers wallbox to be installed on the stand, we can provide the matching one.

Specification

Input voltage/Output voltage	AC 230V/400V
Input frequency	50Hz
Max. output power	7.4KW(1 Phase) / 22KW(3 Phase)
Max. output current	32A
Charging interface type	IEC 62196-2, SAE J1772
Over voltage protection	✓
Under voltage protection	✓
Over load protection	✓
Short circuit protection	✓
Earth leakage protection	✓
Over-temp protection	✓
Lightening protection	✓
LCD	3.5-inch color display
RCD	Type A+6mA DC
LED Indicator light	✓
Intelligent power adjustment	✓
Protection degree	IP66
Environment temperature	-40°C ~ +75 °C
Relative humidity	0-95% non-condensing
Maximum altitude	<2000m
Cooling	Natural air cooling
Standby power consumption	<8W
Dimension (W/H/D)	295/195/65mm
Weight	6KG~8KG
Wall-mounting bracket	✓
Ground-mounting pole	Optional
Certificate	CE, TUV, FCC, CSA, RoHS, RCM

OCULAR

